

DATOS TÉCNICOS


Flexco Unión tipo	Espesor de la cinta	Diámetro mínimo de polea	PIW Máximo
UNIÓN R2	3-10mm	127mm	330
UNIÓN R5	6-11mm	230mm	450
UNIÓN UX-1 S12 UNIBAR-430	3.2- 4.0mm	51mm	75
UNIÓN U-2 S12 UNIBAR-430	4.0- 4.8mm	51mm	125
UNIÓN U-3 S12 UNIBAR-430	4.8- 5.6mm	76mm	125
UNIÓN U-4 S12 UNIBAR-430	5.6- 6.4mm	102mm	125
UNIÓN U-5 S12 UNIBAR-430	7.1- 7.9mm	127mm	125
UNIÓN U-6 S12 UNIBAR-430	7.9- 9.0mm	152mm	125
UNIÓN 62 ALLIGATOR GALV/ INOX	1.5- 3.2mm	50mm	125
UNIÓN 125 ALLIGATOR GALV/INOX	3.2- 4.8mm	75mm	150
UNIÓN 187 ALLIGATOR GALV/INOX	4.8- 6.4mm	100mm	200
UNIÓN 27 ALLIGATOR	5.6- 7.1mm	125mm	100
UNIÓN 45 ALLIGATOR	7.9- 9.5mm	229mm	160
UNIÓN 55 ALLIGATOR	9.5- 11.1mm	305mm	172
UNIÓN ARJ7 ALLIGATOR RIVET	5.1- 6.0mm	88mm	300
UNIÓN PLACA PERNO 1 1/2" E	11.1- 17mm	406mm	150
UNIÓN PLACA PERNO 2"E	14- 21mm	711mm	450
UNIÓN PLACA PERNO 2 1/2" E	19- 25mm	1067mm	560
HINGED PLATE GRIP X 500 / X500S	6-16mm	230mm	300



Unión R5



Clipper ux-2



Alligator 125




unibar ux-2



Rivet ARJ7



Hinged plated X 500/s



Inst. 6-24"



Set ST3.9



Placa Perno



HERRAMIENTAS

HERRAMIENTA INST. 6- 24"

HERRAMIENTA STAPLE DRIVE ST3-9